



Chainsaw Oil

Product Description

Chainsaw Oil is specifically developed for the lubrication of chain and guide bars of modern chain saws. Selected mineral base oils are combined with special additives to provide good protection against wear, rust and corrosion. Chainsaw Oil has good low temperature flow properties which makes it suitable for outside applications even during the winter season.

Features and Benefits

Features	Advantages and Potential Benefits
Good adherence to metal surfaces	Stays well in place on saw chains and guide bars and ensures optimum component lifetime
Excellent protection against wear, rust and corrosion	Contribution toward increased chain and guide bar life and reduced maintenance costs as wear related failures are reduced
Low pour point	Ensures flow ability even at low operating temperatures for higher efficiency

Applications

Chainsaw Oil can be used in hand-held or machine operated chain saws as specified by the manufacturer. It is suitable for lubrication of chains, slideways and guides in industrial applications, where a lubricant with good adherence, protection against wear, rust and corrosion and a low pour point is required.

Typical Properties

Chainsaw Oil	
Viscosity, ASTM D 445	
cSt@40°C	87
cSt@100°C	11
Pour Point, °C, ASTM D 97	-24
Flash Point, °C, ASTM D 92, min.	220
Specific Gravity @ 15.6°C, kg/l, ASTM D4052	0.877

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL,
BVBA (EMPC)
POLDERDIJKWEG
B-2030 Antwerpen
Belgium

Automotive products: 0800 0229118
Industrial products: 0800 0229120
Fax: 0800 0229222

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

© 2001-2010 Exxon Mobil Corporation. All rights reserved.