



## Mobil Zerice S Series

### Refrigeration Compressor Lubricants

#### Product Description

Mobil Zerice S Oils are premium quality synthetic refrigeration compressor lubricants. Based on alkyl benzenes, which due to their nature, have superior miscibility with hydrochlorofluorocarbon (R22), as well as chlorofluorocarbon refrigerants (R 502 and R 12: possibly used on some old refrigerating plants). This allows them to be used in very low temperature applications, down to -60C.

#### Features, Advantages and Benefits

Relative to mineral and other synthetic lubricants, Mobil Zerice S has superior solubility with halocarbon refrigerants. This helps avoid the common problem of oil separation and congealing on the valve and heat transfer surfaces of the refrigeration system.

Additionally, Mobil Zerice S lubricants have very low pour and floc points which helps prevent harmful wax precipitation that can block expansion valves and heat transfer surfaces.

Mobil Zerice S lubricant's synthetic nature provides excellent chemical stability and resists reaction with refrigerants and high thermal stability which helps prevent oil breakdown.

Features	Advantages and Potential Benefits
Miscibility with halocarbon refrigerants	Increased system efficiency
Low pour and floc points	Avoids wax precipitation and increased system efficiency
Chemical Stability	Long oil service life

#### Applications

Mobil Zerice S lubricants are recommended for all refrigeration compressor types, reciprocating or rotary screw types. They are well suited for use with fluorocarbon refrigerants. They should not be used with sulfur dioxide or R134A refrigerants. The specific viscosity grade should be selected in accordance with the compressor manufacturer's recommendations.

#### Typical Properties

Mobil Zerice S	68	100
Viscosity, ASTM D 445		
cSt @ 40°C	68	100
cSt @ 100°C	6.5	8.0
Pour Point, °C, ASTM D 97	-27	-27
Flash Point, °C, ASTM D 92	174	186
Floc Point, R12, °C	-60	-60
Acid Number, mg/KOH, max., ASTM D 974	.05	.05
Copper Corrosion 3 h, at 100 °C, ASTM D 130	1	1
Water Content, ppm, ASTM D 1533	<50	<30

#### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed.

MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The ExxonMobil logotype and Zerice are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

ExxonMobil Marine Limited  
Ermyrn Way  
Leatherhead, Surrey  
United Kingdom KT22 8UX

<http://www.exxonmobil.com>

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001-2010 Exxon Mobil Corporation. All rights reserved.