



## Mobil Agri Super 15W-40

### Super Tractor Oil Universal (STOU) Lubricant

#### Product Description

Mobil Agri Super 15W-40 is a high performance, multi-functional lubricants for most farm equipment application. This STOU lubricant provides good performance in diesel and gasoline engines, transmissions, hydraulics, final drives, and oil-immersed brakes operating in agricultural service. Mobil Agri Super is recommended for use in a wide range of heavy-duty applications and operating environments found in the farming industry.

#### Features and Benefits

Agricultural enterprises employ a wide variety of equipment requiring multi-functional lubrication performance. The engineering in Mobil Agri Super 15W-40 meets the diverse lubrication requirements of this equipment which reduces the number of lubricants required and the possibility of misapplication. The key benefits include:

Features	Advantages and Potential Benefits
Good thermal and oxidation stability	Reduced sludge build-up and high temperature deposits
TBN reserves	Improved deposit control
Good rust and corrosion protection	Reduced wear and long equipment life especially in hydraulic components
Effective detergency/dispersancy	Cleaner engines and long engine life
High temperature viscosity retention and volatility control	Reduced engine scuffing, bore polishing, and oil consumption
Unique frictional and load carrying properties	Increased power, improved power train performance, and elimination of chatter in wet brakes
Low temperature pumpability and performance	Easier engine start-up, reduced wear in critical valve train, and good hydraulic response
Component compatibility	Longer gasket and seal life
Multipurpose product	Reduces inventory and chance for misapplication

#### Applications

- Mixed diesel and gasoline-powered farm vehicles and equipment
- Farm equipment transmissions and power systems requiring multifunctional fluid

#### Specifications and Approvals

Mobil Agri Super Multigrades has the following builder approvals:	15W-40
ZF-TE-ML 06B/07B	X

Mobil Agri Super Multigrades are recommended by ExxonMobil for use in applications requiring:	15W-40
Allison C-4 (Agriculture Applications Only)	X
Massey Ferguson MF 1139, 1144, 1145	X
API CF	X
API CF-4/SF	X
API GL-4	X
Caterpillar TO-2	X
John Deere J27	X
Ford New Holland M2C 159B	X

## Typical Properties

<b>Mobil Agri Super Multigrades</b>	
SAE Grade	15W-40
Viscosity, ASTM D 445	
cSt @ 40°C	96.0
cSt @ 100°C	14.2
Viscosity Index, ASTM D 2270	140
Sulfated Ash, wt%, ASTM D 874	1.5
Total Base # , mg KOH/g, ASTM D 2896	11.2
Pour Point, °C, ASTM D 97	-30
Flash Point, °C, ASTM D 92	220
Density @ 15°C kg/l, ASTM D 4052	0.88

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed.

MSDS's are available upon request through your sales contract office, or via the Internet on (insert Internet address here). This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Agri Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

9-2010

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL,  
BVBA (EMPC)  
POLDERDIJKWEG  
B-2030 Antwerpen  
Belgium

Automotive products: 0800 0229118

Industrial products: 0800 0229120

Fax: 0800 0229222

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com) ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

© 2001-2010 Exxon Mobil Corporation. All rights reserved.