



Mobil Super FE Special 5W-30

Premium Quality Multigrade Synthetic Motor Oil

Product Description

Mobil Super FE Special 5W-30 is a premium quality synthetic engine oil developed to the highest standards of lubricant quality, reliability and dependable protection.

Features and Benefits

Mobil Super FE Special 5W-30 is formulated with a proprietary mixture of premium and super premium quality synthetic base oils with additive technology that provides outstanding engine protection under a variety of operating conditions. Key features and benefits include:

- Excellent oxidation stability to reduce engine deposits and sludge build-up to keep engines running reliably
- Excellent high and low temperature properties to provide dependable protection across a wide range of driving conditions
- Enhanced low temperature capabilities for outstanding cold weather starting

Applications

Mobil Super FE Special 5W-30 can be used in a variety of gasoline and diesel automobiles, light trucks and vans, and for anyone seeking a dependable super premium quality product.

Specifications and Approvals

Mobil Super FE Special 5W-30 meets or exceeds the requirements of:

API SL	X
Ford WSS-M2C913-A	X
Ford WSS-M2C913-B	X

Mobil Super FE Special 5W-30 is recommended by ExxonMobil for use in applications requiring:

ILSAC GF-3	X
------------	---

Typical Properties

Mobil Super FE Special 5W-30

Viscosity, ASTM D 445	
cSt @ 40° C	58.6
cSt @ 100° C	10.6
Sulfated Ash, wt%, ASTM D 874	1.05
Phosphorous	0.1
Flash Point, °C, ASTM D 92	225
Density @15° C kg/l, ASTM D 4052	0.85
Pour Point, °C, ASTM D 97	-51

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

9-2010

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL,
BVBA (EMPC)
POLDERDIJKWEG
B-2030 Antwerpen
Belgium

Automotive products: 0800 0229118

Industrial products: 0800 0229120

Fax: 0800 0229222

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

© 2001-2010 Exxon Mobil Corporation. All rights reserved.